



| | | | | | | |
|--------------------|----------------------|---------------|-------------------|----------------------------|----------------------|--|
| 03 | | | | Description: V凸 | |  金艾科 JINAIKE |
| 02 | | | | Size: 2.3×1.4 (1.4×0.6) | | |
| 01 | | | | Material: SUS | Hardness: HV1 440 | |
| Rev. | Revision description | Designed by | Date | Drawing No.: | | JAK0689 |
| Designed by: | Date: | Approved by: | Date: | Revision: | Unit of length: | |
| Wenjun Kang | 15/04/2024 | Lei Gu | 15/04/2024 | T0 | mm |  |

| Tolerance for linear dimensions extract from IOS 2768-1 | | | | Tolerance for angular dimensions extract from IOS 2768-1 | | | | Permissible deviations for lengths in millimeters of shorter side of the angle concerned |
|---|------------------|-----------------|-------------------|--|----------|------------------|-------------------|--|
| Designation | from 0.5 up to 6 | from 6 up to 30 | from 30 up to 120 | Designation | up to 10 | from 10 up to 50 | from 50 up to 120 | |
| fine | ±0.05 | ±0.1 | ±0.15 | fine | ±1° | ±0°30' | ±0°20' | |

This drawing is exclusive ownership of JINAIKE. No part of this drawing may be reproduced or published, without written permission of JINAIKE